

SA Rod end SAL35-ES-2RS-DURBAL - SAL35-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal35-es-2rs-durbal>

SAL35-ES-2RS



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Bad end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 35 ES (-2RS)	35	M 36 x 3	25	21,0	82

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 35 ES (-2RS)	82	41	140	6	146,0	1,400

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498423
Inside diameter	35 mm
Outside diameter	82 mm
Thickness	25 mm
Type	SA
Weight	1400 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE