

SA Rod end SA60-ES-2RS-DURBAL - SA60-ES-2RS-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sa60-es-2rs-durbal>

SA60-ES-2RS



**male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E**

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

| order number | | measurement [mm] | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ |
| SA 60 ES (-2RS) | | 60 | M 52 x 3 | 44 | 38,0 | 135 |

| type | measurement [mm] | | | | n [°] | load rating C ₀ [kN] | weight [kg] |
|-----------------------|--------------------|----------------|-----|---|----------|---------------------------------------|----------------|
| | l ₁ min | l ₂ | h | | | | |
| SA / SAL 60 ES (-2RS) | 115 | 60 | 210 | 6 | 6 | 450,0 | 5,900 |

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DURBAL |
| N° Ean13 | 3663952498799 |
| Inside diameter | 60 mm |
| Outside diameter | 135 mm |
| Thickness | 44 mm |
| Type | SA |
| Weight | 5900 g |
| Thread | Right-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE