

SA Rod end SAL80-ES-DURBAL - SAL80-ES-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/sal80-es-durbal>

SAL80-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 80 ES	80	M 64 x 4	55	47,0	180	

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 80 ES	140	90	270		6	750,0	12,000

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952498911
Inside diameter	80 mm
Outside diameter	180 mm
Thickness	55 mm
Type	SA
Weight	12000 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE