


TAPR Rod end GIHO-K-30DO-DURBAL - GIHO-K-30DO-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/tapr/giho-k-30do-durbal>

GIHO-K-30DO 

Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. E5 pressed into rod end housing. Sliding combination steel/steel with grease nipple.


Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required



order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-K 30 DO		30	34,2	80	M 20 x 1,5	36	77	22	19	19	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500768
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	19 mm
Type	TAPR
Weight	1250 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE