

TAPR Rod end GIHO-K-40DO-DURBAL - GIHO-K-40DO-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/tapr/giho-k-40do-durbal>

GIHO-K-40DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number	measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂
GIHO-K 40 DO		40	45,0	100	M 27 x 2	45	90	28	23	23

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHN-K / GIHN-KL 40 DO	105	37	155,0	45	7	156,0	2,16

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500812
Inside diameter	40 mm
Outside diameter	100 mm
Thickness	23 mm
Type	TAPR
Weight	2160 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE