

TAPR Rod end GIHO-KL-80DO-DURBAL - GIHO-KL-80DO-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/tapr/giho-kl-80do-durbal>

GIHO-KL-80DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/ steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	right hand thread	left hand thread	measurement [mm]						
GIHO-KL 80 DO	80	89,4	205	M 48 x 2	90	156	55	47	47

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHN-K / GIHN-KL 80 DO	185	64	287,5	82	6	585,0	15,00

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952500935
Inside diameter	80 mm
Inside diameter	3.15" inch
Outside diameter	205 mm
Outside diameter	8.071" inch
Thickness	47 mm
Thickness	1.85" inch
Type	TAPR
Weight	15000 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE