

GEG Rod end GE20-LO-DURBAL - GE20-LO-DURBAL


<https://www.123bearing.co.uk/bearing-housing/rod-end/geg/ge20-lo-durbal>

GE20-LO



Description: spherical plain bearing with sliding combination steel / steel. Inner ring with cylindrical extension at both sides. Lubrication groove and hole in inner and outer ring. Outer ring of type DGE...HO-2RS with two seals.

spherical plain bearing; similar to DIN ISO 12240-1, series W



Sliding combination:

steel / steel

Inner ring: bearing steel, hardened, ground and phosphated, with cylindrical extension on both sides

Outer ring: bearing steel, hardened, ground and phosphated, single split in axial direction

Lubrication: lubrication required

order number	d	B	C	d ₁ min	D
GE 20 LO	20	20	12	25.0	35

type	measurement [mm]		d ₁	r ₁	load rating C ₁₀ [N]	weight [kg]
	r ₁ min	r ₂ min				
GE 20 LO	0.3	0.3	29.0	4	146	0.070

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952506395
Inside diameter	20 mm
Inside diameter	0.787" inch
Outside diameter	35 mm
Outside diameter	1.378" inch
Thickness	20 mm
Thickness	0.787" inch
Type	GEG
Weight	70 g
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE