

SA Rod end BRTM25-00-502-DURBAL - BRTM25-00-502-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/brtm25-00-502-durbal>

BRTM25-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
type	type hard thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₆	b ₁	b ₂	b ₃	
BRTM 25 -00	-502		25	M 24 x 2		29,5	64		31		22
		measurements [mm]									
type	h	l	b ₃	α	weight	rotational speed limit	basic load rating	dyn.	stat.		
BRTM 25	94	57	30	5,0	0,596	600	C	C ₀	C ₁₀	[N]	[N]

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952506784
Inside diameter	25 mm
Inside diameter	0.984" inch
Outside diameter	64 mm
Outside diameter	2.52" inch
Thickness	31 mm
Thickness	1.22" inch
Type	SA
Weight	596 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE