

## SI Rod end BRF30-00-501-DURBAL - BRF30-00-501-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/brf30-00-501-durbal>

**BRF30-00-501**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

**inner ring:**  
ball bearing steel, hardened, superfinished.

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10)  
DIN 71 412 H1 (sizes 12 to 30)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	right-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	h		
BRF 30 -00	-501	30	40,0	M 30 x 2	34,5	70	50	37	25,0	110		
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.		
type	l	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	β [g]	γ	ν <sub>0</sub>	c	c <sub>0</sub>	C <sub>10</sub>	C <sub>50</sub>
BRF 30	51	15,0	35	41	7,5	0,978	2,24	2,35	450	14150	7450	

### PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507347
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	SI
Weight	978 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE