

## SI Rod end PF15-00-502-DURBAL - PF15-00-502-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/pf15-00-502-durbal>

### PF15-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3485 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread;**  
long-term lubrication, low maintenance, shields

order number		measurements [mm]											
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>			
PF 15 -00		-502	15	19	M 12	17,5	40	16,5	12				
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating								
type	h	l	l <sub>1</sub>	r	SW	α	α <sub>1</sub>	[kg]	Y	%	lim [min]	C [kN]	stat. C <sub>0</sub> [kN]
PF 15	51	24	20,0	15	17	7,0	0,140	2,30	2,41		1025	5000	1890

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507385
Inside diameter	15 mm
Outside diameter	40 mm
Thickness	16.5 mm
Type	SI
Weight	140 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE