


## SA Rod end PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/pm05-01-502-durbal>


### PM05-01-502



**male thread:**  
long-term lubrication, low maintenance, shields



**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]					measurements [mm]					weight		calculation factors		rotational speed limit		basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.	C0	C0	
PM 05 -01	-502	5	M 8 x 1		7.5	19	12	12	12	8										
type		l1	l2	l3	h1	h2	u	z	alpha [°]											
PM 05	16	13	33.5		1.5	2.5	7.0							0,033	1,51	1,58	1350	1610	480	

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507446
Inside diameter	5 mm
Outside diameter	19 mm
Thickness	12 mm
Type	SA
Weight	33 g
Thread	Left-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE