

SA Rod end PM10-03-501-DURBAL - PM10-03-501-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/pm10-03-501-durbal>

PM10-03-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]	
type	type	type	type
PM 10 -03 -501	10	M 14 x 1,5	12,5
			36
			19
			20
			14

measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating	stat.						
type	type	type	type	type	type	type						
PM 10	26	28	58,5	2,5	2,5	9,5	0,154	1,69	1,77	1100	5120	1905

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507576
Inside diameter	10 mm
Outside diameter	36 mm
Thickness	20 mm
Type	SA
Weight	154 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE