

## SA Rod end PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/sa/pm15-02-501-durbal>

### PM15-02-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]			measurements [mm]			weight			rotational speed limit			basic load rating		
type	spc/hand/thread	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min <sup>-1</sup> ]	C [N]	C0 [N]	
PM 15 -02	-501	15	M 20 x 1.5	18.5	42	26	20	14								
measurements [mm]		weight		rotational speed limit		basic load rating										
type	l1	l2	l3	h1	h2	u	z	alpha [°]	weight [kg]	Y	Yc	nmax [min <sup>-1</sup> ]	C [N]	C0 [N]		
PM 15	36	30	73.5	3.0	2.5	6.5	0.273		2.07	2.17		975	5485	3270		

## PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952507651
Inside diameter	15 mm
Outside diameter	42 mm
Thickness	20 mm
Type	SA
Weight	273 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE