

SI Rod end BEF30-20-502-DURBAL - BEF30-20-502-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/bef30-20-502-durbal>

BEF30-20-502



rod end housing:
forged steel, tempered, surface galvanized, free of Cr VI


joint ball:
ball bearing steel, hardened and ground, surface superfinished and chromium plated

race:
nylon / teflon / glass fibre compound

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral spherical plain bearing

female thread:
maintenance free, adapter sizes according to DIN ISO 12240-4, series K, thread according to ISO 8139



order number		measurements [mm]										
type	spec. hard thread, left-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	b ₁	b ₂	b ₃
BEF 30	-20	-502	30	40,0	M 30 x 2	70	50	50,75	37	25,0		
measurements [mm]		weight										
type	h	l	l ₁	l ₂	l ₃	SW	α ₁ [°]	α ₂ [°]	weight [kg]		basic load rating dyn. stat. [N]	
BEF 30	110	51	15,0	35	41		17,0	10,5	1,084		55010 145600	

PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952508269
Inside diameter	30 mm
Outside diameter	70 mm
Thickness	37 mm
Type	-
Weight	1084 g
Thread	-
Lubrication	-
Packaging	-

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE