

## SI Rod end BRTF1-1-00-501-DURBAL - BRTF1-1-00-501-DURBAL

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/brtf1-1-00-501-durbal>

**BRTF1/1-00-501**

**red end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 71 412 H1

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning roller bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, dimensions in inches

order number		measurements [inches]									
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>
BRTF 1/1 -00	-501		1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866	
		measurements [inches]									
type	h	l	l <sub>1</sub>	l <sub>2</sub>	SW	α	weight	rotational speed limit	basic load rating	stat. C <sub>10</sub>	stat. C <sub>1</sub>
BRTF 1/1	3.720	1.653	.236	1.279	1.181	5,0	0,568	600	24900	18500	

### PRODUCT FEATURES

Brand	DURBAL
N° Ean13	3663952510071
Inside diameter	25.4 mm
Outside diameter	63.98 mm
Thickness	30.99 mm
Type	SI
Weight	568 g
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE