


## Drawn cup roller clutches FCBN-6-K-NADELLA - FCBN-6-K-NADELLA

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup-roller-clutch/fcfn-6-k-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page.  
Types FCBL and FCBL clutch and bearing assemblies have stainless steel springs inserted in the molded cage to position rollers for instantaneous lockup.



Shaft Ø mm	Designation	F <sub>w</sub> mm	D mm	C mm	Torque Nm	Load ratings 1)		Overrun limiting speed rating for rotating shaft min <sup>-1</sup>
						Dynamic C <sub>d</sub> kN	Static C <sub>s</sub> kN	
6	FCBN-6-K	6	12	10	0.56	2.48	1.48	22000

Shaft Ø mm	Gaging				Z Minimum outer diameter of steel housing for Torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gag mm	Clutch locking plug mm	Clutch overrun and bearing go plug mm	Bearing no go plug mm		Mounting		Mounting		
	Max. mm	Min. mm	Max. mm	Min. mm	Max. mm	Min. mm	Max. mm	Min. mm		
6	11.980	5.977	6.004	6.030	18	6.000	5.995	11.991	11.980	0.004

## PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3663952529523
Inside diameter	6 mm
Outside diameter	12 mm
Thickness	10 mm
Weight	4 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE