


Drawn cup roller clutches FCB-25-NADELLA - FCB-25-NADELLA

<https://www.123bearing.co.uk/bearing-housing/needle-roller-bearing/drawn-cup-roller-clutch/fcb-25-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page.
Types **FCB** and **FCBL** clutch and bearing assemblies have stainless steel springs inserted in the molded cage to position rollers for instantaneous lockup.



Shaft Ø mm	Designation	F _w mm	D mm	C mm	Torque Nm	Load ratings 1)		Overrun limiting speed rating for rotating shaft min ⁻¹
						Dynamic C _d kN	Static C _s kN	
25	FCB-25	25	32	30	71.0	11.3	13.1	8700

Shaft Ø mm	Gaging				Z Minimum outer diameter of steel housing for Torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun and bearing go plug mm	Bearing no go plug mm		Mounting		Mounting		
	Max. mm	Min. mm	Max. mm	Min. mm	Max. mm	Min. mm	Max. mm	Min. mm		
25	31.972	24.967	25.007	25.043	46	25.000	24.991	31.988	31.972	0.048

PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3663952529592
Inside diameter	25 mm
Outside diameter	32 mm
Thickness	30 mm
Weight	48 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE