


Other bearings AXNAT638-NADELLA - AXNAT638-NADELLA

<https://www.123bearing.co.uk/bearing-housing/other-bearings/axnat638-nadella>

Precision combined bearings, with adjustable axial preload



AXNA and AXNAT series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw DIN 913

Shaft Ø mm	Designation		d mm	D mm	F _d mm	D _m mm	B mm	C mm	B ₁ mm	r mm	Mounting				
	AXNA	AXNAT									Screw TCEB ¹⁾ class 12.9	N° screws	E mm	Torque Nm	
6		638	6	22	8.9	22	15.3	16	6	5	0.35	4 x 12	4	30	3

Load Ratings kN				Speed Ratings min ⁻¹	Preload ¹⁾ N	Rotation ²⁾ torque Nmm	Rigidity K ³⁾ N/mm	Shaft threading	Weight kg	Designation
radial	axial									
Dyn. C	Stat. Co	Dyn. C	Stat. Co							
4.9	5.8	7.2	17.5	15 500	340	70	50	6 x 1	0.064	AXNAT 638

PRODUCT FEATURES

Brand	NADELLA
N° Ean13	3663952530086
Inside diameter	6 mm
Inside diameter	0.236" inch
Outside diameter	22 mm
Outside diameter	0.866" inch
Thickness	16 mm
Thickness	0.63" inch
Weight	64 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE