

Other bearings

AXNBT1560-NADELLA - AXNBT1560-NADELLA

https://www.123bearing.co.uk/bearing-housing/other-bearings/axnbt1560-nadella

**Precision combined bearings,
with adjustable axial preload**



AXNBT and ARNBT series



- 1) 6% of dynamic axial load
- 2) with axial load equal to preload
- 3) rigidity of a single thrust bearing with load equal to preload
- 4) hexagon socket shallow head cap screw (DIN 91)

| Shaft Ø mm | Designation | | | d mm | D mm | D _m mm | D _m mm | B mm | C mm | B ₁ mm | r mm | r ₁ mm | Screw TCE-H class 12.9 | Mounting | | | Torque Nm | |
|------------------|-------------------|-------------------|-------------------|---------|---------|----------------------|----------------------|---------|---------|----------------------|---------|----------------------|------------------------------|------------|---------|---------|--------------|----|
| | AXNBT series 1 | ARNBT series 1 | ARNBT series 2 | | | | | | | | | | | N° viti | E mm | e mm | | |
| 15 | 15 60 | | | 15 | 60 | 20 | 35 | 26.8 | 40 | 16 | 12 | 0.85 | 0.85 | 6x20 | 6 | 48 | 9 | 10 |

| Load Ratings kN | | | | Speed rating min ⁻¹ | Preload ¹⁾ N | Rotation ²⁾ torque Nmm | Rigidity K to N/mm | Weight kg | Designation |
|-----------------|----------|--------|----------|-----------------------------------|----------------------------|---|-----------------------|--------------|-------------|
| radial | | axial | | | | | | | |
| Dyn. C | Stat. Co | Dyn. C | Stat. Co | | | | | | |
| 18.2 | 22.0 | 12.0 | 40.0 | 9 000 | 735 | 120 | 1 250 | 0.406 | AXNBT 15 60 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | NADELLA |
| N° Ean13 | 3616060472625 |
| Inside diameter | 15 mm |
| Outside diameter | 35 mm |
| Thickness | 40 mm |
| Weight | 406 g |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE