


Other rod ends MHL-12-F-DUNLOP - MHL-12-F-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/other/mhl-12-f-dunlop>

MALE ROD ENDS **DUNLOP**



MHL-12F



MH SERIES: MH - MHS - MH SS

Description:
MH series is our 3-piece unique internationally patented range of male rod ends incorporating a polyurethane bearing race that provides ultra smooth operation. A nitroce surface protected ball with a PTFE lubricant provide superior shock load and extended wear properties, combined with excellent chemical and corrosion resistance. The unique innovative captive body design prevents detachment through excessive axial loads. For optimum performance, ensure that the rod end is mounted with the moulded lettering facing away from the direction of pull.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate. Race: Polyurethane. Ball: 230M07PB nitroce finish. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303C. Lubricant: UniFor Oil.

Features:
Metric & imperial sizes
Ultra low friction
High shock loads
Extended wear life
No maintenance
Shielded option

Possible Applications:
Light to medium
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control
Safety features

Temperature Range:
-40°C to + 80°C

Specification:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MHL-12F		3/4	3/4 BSF	0.875	0.689	1.75	2.875	1.75	0.978	52,000

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3663952556758
Inside diameter	19.05 mm
Inside diameter	3/4" inch
Outside diameter	44.45 mm
Outside diameter	1 3/4" inch
Thickness	17.501 mm
Thickness	0.689" inch
2nd Thickness	22.225 mm
2nd Thickness	7/8" inch
Type	SA
Thread	Left-hand thread
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE