


## Deep groove ball bearing single row 1603-SS-NICE - 1603-SS-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/1603-ss-nice>

**1600** Series™ Precision Ground Radial Bearings **NICE**



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
1603™				SS		+0.000 +0.000 -0.005 -0.013	+0.000 +0.000 -0.005 -0.013
						0.3135 7.938	0.8750 22.225
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (g)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)	
0.2813 7.150	644 2866	255 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.012 0.30	

Width for sealed versions = 0.3438 (8.733)      Weights given are for greased and sealed versions

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952556987
Inside diameter	7.938 mm
Outside diameter	22.225 mm
Thickness	7.15 mm
Weight	10 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE