

Deep groove ball bearing single row 1628-DS-NICE - 1628-DS-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/1628-ds-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.0005 -0.013
1628™			DS			0.9250 15.875	1.8250 41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W ⁰ (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5000 12.700	2595 11548	1010 4495	0.18 0.08	0.845 21.46	1.446 36.73	0.025 0.64

ⓘ Weights given are for greased and sealed versions

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952557526
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	12.7 mm
Thickness	1/2" inch
Weight	80 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE