

## Deep groove ball bearing single row 1640-SC-NICE - 1640-SC-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/1640-sc-nice>

**1600** Series™ Precision Ground Radial Bearings (con't) **NICE**



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
1640™		SC				+0.000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.0005 -0.013
						0.9750 22.225	2.0000 50.800

  

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.5625 14.288	2967 13203	1350 6008	0.29 0.13	1.113 28.27	1.780 44.70	0.035 0.89

Weights given are for greased and sealed versions

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952557786
Inside diameter	22.225 mm
Outside diameter	50.8 mm
Thickness	14.288 mm
Weight	130 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE