

Deep groove ball bearing single row 3004-SS-NICE - 3004-SS-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/3004-ss-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LAW RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3004™					SS	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 ⓐ

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2813 ⓑ 7.1450	325 1448	250 1135	0.03 0.01	0.474 12.04	0.778 19.76	0.015 0.38

ⓐ Width for sealed versions = 0.3438 (8.733) ⓑ Weights given are for greased and sealed versions
ⓐ 3038 and larger +0.0005/-0.0006 (+0.001/-0.15)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558110
Inside diameter	9.525 mm
Inside diameter	3/8" inch
Outside diameter	22.225 mm
Outside diameter	7/8" inch
Thickness	7.145 mm
Thickness	0.281" inch
Weight	10 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE