# Deep groove ball bearing single row
# 3004-DS-NICE - 3004-DS-NICE

https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/3004-ds-nice



3000 Series® Semi-Ground Radial Bearings

NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---|---|---|---|---|---|---|---|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) +.005 +0.13 -.000 -.00 | O.D. D (in) (mm) +.0000 +.00 -.0005 -0.013 |
| 3004™ | | | DS | | | 0.3750 9.525 | 0.8750 22.225 |

| | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|---|---|---|---|---|---|---|
| WIDTH B (in) (mm) +.005 +.00 -.005 -.13 | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | W (lbs) (kg) | $d_a$ min (in) (mm) | $D_a$ max (in) (mm) | r max (in) (mm) |
| 0.2813 7.1450 | 325 1448 | 255 1135 | 0.03 0.01 | 0.474 12.04 | 0.778 19.76 | 0.015 0.38 |

Width for sealed versions = 0.3438 (8.733)

Weights given are for greased and sealed versions

3038 and larger +.0000/-.0006 (+.000/-.015)

## PRODUCT FEATURES

| | |
|---|---|
| Brand | NICE |
| N° Ean13 | 3663952558127 |
| Inside diameter | 9.525 mm |
| Outside diameter | 22.225 mm |
| Thickness | 7.145 mm |
| Weight | 10 g |
| Packaging | 1 |

contact@123bearing.co.uk
02038 087 274
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE