

## Deep groove ball bearing single row 3033-SC-NICE - 3033-SC-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/3033-sc-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.13 -0.000 -0.013	O.D. D (in) (mm) +0.000 +0.00 -0.0005 -0.013
3033™		SC				0.6250 15.875	1.7000 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1025 4561	0.22 0.10	0.845 21.46	1.530 38.86	0.025 0.64

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3038 and larger +0.0005/-0.005 (+0.001/-0.13)

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558738
Inside diameter	15.875 mm
Outside diameter	44.45 mm
Thickness	12.7 mm
Weight	100 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE