

Deep groove ball bearing single row 3040-DC-NICE - 3040-DC-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/3040-dc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3040™	DC					+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.013 -0.005
						0.8750 22.225	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6598	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558851
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	50.8 mm
Outside diameter	2" inch
Thickness	14.288 mm
Thickness	9/16" inch
Weight	130 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE