


Deep groove ball bearing single row 400-6V-NICE - 400-6V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/400-6v-nice>

400 Series® Single Row. Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	6V	0.375 +0.0004-0.0008 9.53 +0.01 9.22	0.875 +0.0004-0.0008 22.23 +0.01 21.23	0.250 +0.0109-0.0110 6.35 +0.28 6.07	0.250 Reference 6.35	14	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.03	156 (N)	108 (N)	75 (N)	60 (N)	42 (N)	30 (N)
0.01	694	481	334	267	187	134

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952559995
Inside diameter	9.53 mm
Outside diameter	22.23 mm
Thickness	6.35 mm
Weight	10 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE