


Deep groove ball bearing single row 404-16V-NICE - 404-16V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/404-16v-nice>

400 Series® Single Row. Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
404™	16V	0.375 9.53 +0.0004-0.0008 -0.131-0.00	1.062 26.97 +0.0009-0.0009 -0.191-0.00	0.250 6.35 +0.0119-0.0110 -0.251-0.00	0.250 6.35 Reference	16	16 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.04 0.02	178 792	124 552	85 378	69 307	48 214	34 151

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560021
Inside diameter	9.53 mm
Outside diameter	26.97 mm
Thickness	6.35 mm
Weight	20 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE