


## Deep groove ball bearing single row 400-20V-NICE - 400-20V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/400-20v-nice>

**400 Series® Single Row Unground Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	20V	0.375 9.53	1.125 28.58	0.375 9.53	0.375 9.53	18	1/8 3.18

WEIGHT (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.08 0.04	200 890	139 619	96 427	78 347	54 243	38 168

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560045
Inside diameter	9.53 mm
Inside diameter	3/8" inch
Outside diameter	28.58 mm
Outside diameter	1 1/8" inch
Thickness	9.53 mm
Thickness	3/8" inch
Weight	40 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE