


Deep groove ball bearing single row 400-23V-NICE - 400-23V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/400-23v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	23V	0.312 7.92 +0.0005-0.0008 +131.00	1.281 32.54 +0.0050-0.0000 +131.00	0.312 7.92 +0.0110-0.0110 +251.20	0.312 7.92 Reference	16	5/32 3.97

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.09 0.04	275 1224	180 809	133 588	107 476	75 334	52 231

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560076
Inside diameter	7.92 mm
Outside diameter	32.54 mm
Thickness	7.92 mm
Weight	40 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE