


## Deep groove ball bearing single row 410-30V-NICE - 410-30V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/410-30v-nice>

**400** Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
410™	30V	0.625 15.88 +0.0002 -0.0004	3.375 84.93 +0.0030 -0.0000	0.470 11.94 +0.0100 -0.0100	0.500 12.70 Reference	16	3/16 4.75

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
0.10	375	261	180	145	101	71
0.05	1989	1161	801	645	449	316

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560113
Inside diameter	15.88 mm
Outside diameter	34.93 mm
Thickness	11.94 mm
2nd Thickness	12.7 mm
Weight	50 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE