


Deep groove ball bearing single row 416-41V-NICE - 416-41V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/416-41v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm) +0.000/-0.0005	B O.D. (in) (mm) +0.005/+0.000	C WIDTH (in) (mm) +0.010/+0.010	D WIDTH (in) (mm) Reference	No.	Size (mm)
416™	41V	1.000 25.40	2.000 50.80	0.572 14.53	0.625 15.88	17	1/4

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.30	757	525	362	293	204	142
0.14	3389	2338	1611	1304	928	632

Notes
Balls - Carbon Steel Grade 200
Rings - Carbon Steel, Case Hardened
Balls - 1010 Carbon Steel, Soft
Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560168
Inside diameter	25.4 mm
Outside diameter	50.8 mm
Thickness	14.53 mm
2nd Thickness	15.88 mm
Weight	140 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE