

Deep groove ball bearing single row 5561-V-NICE - 5561-V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/5561-v-nice>

5000 Series® Single Row. Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5561™	V	0.250 6.35	0.687 17.45	0.250 6.35	0.250 6.35	0.750 19.05	0.250 6.35	0.250 6.35

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
10	1/8	110 3.18	77 2.01	53 1.48	43 1.19	30 0.84	21 0.58

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560212
Inside diameter	6.35 mm
Outside diameter	17.45 mm
2nd Outside diameter	19.05 mm
Thickness	6.35 mm
Weight	10 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE