

## Deep groove ball bearing single row 5507-V-NICE - 5507-V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/5507-v-nice>

**5000 Series® Single Row. Unground Flanged Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5507™	V	0.312 7.92	1.149 28.98	0.365 9.28	0.062 1.57	1.250 31.75	0.125 3.18	0.437 11.10

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
15	5/32 3.97	300 890	139 819	96 427	78 347	54 240	33 169

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560236
Inside diameter	7.92 mm
Outside diameter	28.58 mm
2nd Outside diameter	31.75 mm
Thickness	9.78 mm
2nd Thickness	11.1 mm
Weight	40 g
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE