

Deep groove ball bearing single row 5327-V-NICE - 5327-V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/5327-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
		+0.005/-0.000 +13/-00	+0.005/+0.000 +18/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25
5327™	V	0.550 12.70	1.567 38.10	0.447 11.35	0.092 1.87	1.858 42.06	0.125 3.18	0.531 13.49

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (in) (%)	100 (in) (%)	200 (in) (%)	300 (in) (%)	600 (in) (%)	1200 (in) (%)	
17	3/16 4.75	0.16 0.07	492 2189	342 1522	226 1050	130 846	132 587	92 409

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560281
Inside diameter	12.7 mm
Outside diameter	38.1 mm
2nd Outside diameter	42.06 mm
Thickness	11.35 mm
2nd Thickness	13.49 mm
Weight	70 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE