

Deep groove ball bearing single row 609-V-NICE - 609-V-NICE

<https://www.123bearing.co.uk/bearing-housing/deep-groove-bearing/single-row/609-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- POLY-STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS CLEARANCE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE

BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
609™	V	1.000 25.40	1.075 27.31	1.79 45.40	.630 16.00	12 3/8	0.30 0.14

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1706 7562	1378 6132	1017 4520	551 2452	398 1771	284 1264

Notes
 Balls - Carbon Steel Grade 52100
 Washers - Carbon Steel Case Hard
 Bands - Carbon Steel Soft
 Bearings Oiled with a Rust Preventative
 All Bearings Marked on Band with "Designation Nice USA" as Shown

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952560434
Inside diameter	25.4 mm
Outside diameter	50.8 mm
Thickness	16 mm
Weight	140 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE