

Housed bearing 2 bolts N6908-B-NICE - N6908-B-NICE

<https://www.123bearing.co.uk/bearing-housing/housed-bearing/cast-iron-housed-bearing-2/n6908-b-nice>

6900 Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 3000 - 8000 RPM
- THROUGH HARDNESS
- RETAINER DESIGN
- NYLON RETAINER STANDARD
- SHOULDER BEADED STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

When Ordering specify whether assembly or bearing only is required.
Bearings are stamped with designation and a "B" for example 6908-B. Housing is stamped with the numbers.
Tolerance for 6912 and larger is ± 0.0001 (-0.0001-0.015)

BEARING		PRINCIPLE DIMENSIONS					
FLANGED UNIT	BEARING ONLY SUFFIX	Bore d (in) (mm)	O.D. D (in) (mm)	Width B (in) (mm)	Width C (in) (mm)	E (in) (mm)	F (in) (mm)
		+0.005 -0.005	+0.000 +0.000	+0.000 +0.000			
		+0.000 -0.000	+0.000 -0.000	+0.000 -0.000			
N6908™	B	0.500 12.70	1.6250 41.28	0.900 22.70	1.000 25.40	0.955 24.28	0.500 12.70

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473356
Shaft diameter	12.7 mm
No. of fasteners	2
Tightening	set screw
Mounting center distance	73.03 mm
Material	TOLE
Weight	160 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE