

Housed bearing accessories 7608-DL-NICE - 7608-DL-NICE

<https://www.123bearing.co.uk/bearing-housing/housed-bearing/accessories/7608-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

PRECISION ENGINEERED FOR ALL CONTACT SURFACES SUBJECT TO THE BEARING'S DESIGN

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE: 5000-8000 RPM
- TIMED WASHING
- STEEL CASE STANDARD
- SHIMMEL BEARING STANDARD
- BEARING APPLICABLE SINGLE LIP CONTACT ONLY
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHAFT FUR. OPTION. THIS WILL CHANGE TO AN OPTION
- INDICATED FOR APPLICATIONS WHERE BEARING, SHAFT AND HOUSING ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS								
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)			
7608™	.8000 19.75	1.7500 44.50	0.6250 15.88	0.0625 1.58	1.000 25.40	0.138 3.45			
BEARING Ø	PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT W (kg)
	H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C _d (N)	
0.042 1.07	1.922 48.82	1.992 50.60	0.405 10.29	0.233 5.92	10.32	0.036 0.89	2096 11548	1025 4561	0.38 0.16

When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
Tolerance for 7613™ and larger is +0.000/-0.006 (+0.000/-0.15)
Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC Nice® Bearings.

Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
Weights given are for greased and sealed versions

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473394
Inside diameter	12.7 mm
Outside diameter	25.63 mm
Thickness	15.88 mm
Weight	160 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE