

Housed bearing accessorie 7614-DL-NICE - 7614-DL-NICE

<https://www.123bearing.co.uk/bearing-housing/housed-bearing-accessories/7614-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE MICH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 3000 - 8000 RPM
- PRECISION MANUFACTURE
- STEEL BEARING
- WATER WASH RESISTANT
- STANDARD BEARING HOUSING
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHARP EDGE PROFILE, WITH POOR DIMENSIONS AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE WEIGHT, SIZE, SPEED AND NOISE ARE ESSENTIAL FACTORS TO CONSIDER

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7614™ Ø	+0.008 +0.000 -0.000 -0.000	+0.000 +0.000 -0.005 Ø	+0.000 -0.000	0.0625 1.58	1.308 33.17	+0.005 +0.13 -0.05 -0.13
	Ø19.0 22.23	2.0000 50.80	0.6250 15.88			0.136 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius Ø R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.035 0.89	2970 13217	1350 6098	0.43 0.20

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.000/-0.006 (+0.000/-0.15)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

PRODUCT FEATURES

Brand	NICE
N° Ean13	3616060473455
Inside diameter	22.23 mm
Outside diameter	33.17 mm
Thickness	15.88 mm
Weight	200 g
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE