

# SI Rod end

## FSL-M14-C-DUNLOP - FSL-M14-C-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/fsl-m14-c-dunlop>

**FEMALE ROD ENDS**

**DUNLOP**

**FS SERIES: FS - FSS - FS SS**

**Description:**  
FS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 230M07Pb and forged 680M4s, zinc plated and clear trivalent passivate and stainless steel 302L and forged 304. Inner Ring: Steel 030M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

**Features:**  
Metric & imperial thread & bore sizes, low friction, high shock loads, extended wear life, no maintenance, slotted end stainless steel options.

**Possible Applications:**  
Medium/heavy industrial mechanical applications, construction equipment, agricultural equipment, motor sport and recreational vehicles requiring high precision motion control.

**Temperature Ranges:**  
-200°C to +750°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Steel 230M07Pb (Sizes M08 - M12), Forged 680M4s (Sizes M14 - M20), Zinc Plated and Clear Trivalent Passivate

**Inner Ring:** Steel 030M20, Zinc Plated and Clear Trivalent Passivate

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

**Liner:** High strength PTFE composite

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread   | W  | H     | D  | L1 | L2 | O     | AF | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|----------|----|-------|----|----|----|-------|----|-------------------------------------|
| FS-M14C             |                    | 14        | M14X1.50 | 19 | 13.50 | 36 | 57 | 25 | 16.80 | 22 | 29,200                              |

**Interchange table**

| Dunlop        | Rose | Aurora            | Askubal | SKF   | Asahi   | IKO    | Fluro |
|---------------|------|-------------------|---------|-------|---------|--------|-------|
| FS-M (metric) | MFC  | MW-M-T and MG-M-T | KI-P    | SKB-F | JAF-EC  | PHS-EC | QISW  |
| FS (imperial) | RFC  | MW-T and MG-T     | -       | -     | PHSB-EC | -      | -     |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## PRODUCT FEATURES

|                  |                   |
|------------------|-------------------|
| Brand            | DUNLOP            |
| N° Ean13         | 3616060554222     |
| Inside diameter  | 14 mm             |
| Outside diameter | 19 mm             |
| Thickness        | 13.5 mm           |
| Type             | SI                |
| Thread           | Right-hand thread |
| Lubrication      | with              |
| Packaging        | 1                 |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE