

SI Rod end FSL-08-F-DUNLOP - FSL-08-F-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/fsl-08-f-dunlop>

FEMALE ROD ENDS



FS SERIES: FS - FSS - FS SS

Description:
FS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the lower material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel Z30M07Pb and forged 680M4s, zinc plated and clear trivalent passivate and stainless steel 302L and forged 32L. Inner Ring: Steel 670M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Sludged and stainless steel options.

Possible Applications:
Medium/heavy industrial, mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to 250°C

Specification:
ELV & RoHS compliant

Housing: Steel Z30M07Pb (Sizes 0.625" DP), Forged 680M4s (Sizes 0.625" - 2"), Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Strength PTFE Composite

| Part No. Right Hand | Part No. Left Hand | Bore Size | Thread | W | H | D | L1 | L2 | O | AF | Static Load Rating (Newtons) Radial |
|---------------------|--------------------|-----------|---------|-------|-------|-------|-------|-------|-------|-------|-------------------------------------|
| FSL-08F | | 1/2 | 1/2 BSF | 0.625 | 0.500 | 1.375 | 2.125 | 1.187 | 17.75 | 0.750 | 23,600 |

Interchange table

| Dunlop | Rose | Aurora | Askubal | SKF | Asahi | IKO | Fluro |
|---------------|------|-------------------|---------|-------|---------|--------|-------|
| FS-M (metric) | MFC | MW-M-T and MG-M-T | KI-P | SKR-F | JAF-EC | PHS-EC | QISW |
| FS (imperial) | RFC | MW-T and MG-T | - | - | PHSG-EC | - | - |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCT FEATURES

| | |
|------------------|-------------------|
| Brand | DUNLOP |
| N° Ean13 | 3616060554567 |
| Inside diameter | 12.7 mm |
| Outside diameter | 0.625 mm |
| Thickness | 0.5 mm |
| Type | SI |
| Thread | Right-hand thread |
| Lubrication | with |
| Packaging | 1 |

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE