

SI Rod end FX-16-FG-DUNLOP - FX-16-FG-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/fx-16-fg-dunlop>

FEMALE ROD ENDS DUNLOP




FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No.	Part No.	D	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton)
FX-16G		1.0000	1.375	1.0000	1.375	3.000	4.125	2.125	1.625	1 1/4 UNF	24	150250

Interchange table

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060555328
Inside diameter	10000 mm
Inside diameter	393.701" inch
Outside diameter	1.375 mm
Outside diameter	0.054" inch
Thickness	1 mm
Thickness	0.039" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE