



SI Rod end AL-SA-090-LH-DUNLOP - AL-SA-090-LH-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/al-sa-090-lh-dunlop>

FEMALE ROD ENDS **DUNLOP**

Housing: Aluminum A6061, Black Anodised

Race Ball: GR-Nylon, LV-3H Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminum A6061, black anodised, Race: GR-nylon LV-3H, Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-090-LH		9	M4x0.75	6	4.50	12	19.5	6.0	5.2	6.0	3,040

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556561
Inside diameter	3 mm
Outside diameter	6 mm
Thickness	4.5 mm
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE