





SI Rod end AL-SA-201-LH-DUNLOP - AL-SA-201-LH-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/al-sa-201-lh-dunlop>

FEMALE ROD ENDS 



FEMALE ROD ENDS

AL SERIES

Description:
AL-Series is our 3-piece aluminium light weight range of self-lubricating general purpose female rod ends suitable for light industrial/mechanical load applications requiring low friction, with good wear resistance and available in metric bore and thread sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Aluminium A6061, black anodised. Race: GR-nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features:
Metric bore & thread sizes
Low friction
Self-lubricating
Good wear resistance
Excellent moisture resistance
No maintenance
Light weight

Possible Applications:
Light industrial/mechanical applications
Weight restricted applications
Linear movement sensors

Temperature Range:
-30°C to +170°C

Specification:
ELV & RoHS compliant

Housing: Aluminium A6061, Black Anodised Race: GR-nylon, LV-3H Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating Radial (Newtons)
AL-SA-201LH	9	M4x1.00	9	6.00	16	27.0	13.5	9.0	9.0		5,340

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556769
Inside diameter	5 mm
Inside diameter	0.197" inch
Outside diameter	8 mm
Outside diameter	0.315" inch
Thickness	6 mm
Thickness	0.236" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE