

SI Rod end DB-SA-170-DUNLOP - DB-SA-170-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/db-sa-170-dunlop>

MALE ROD ENDS

DB SERIES: DBM - DBI

Description:
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

Material Specifications:
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

Features: Metric & imperial thread & bore sizes Low friction Self-lubricating Good wear resistance Excellent moisture resistance No maintenance	Possible Applications: Light to medium/heavy industrial/mechanical applications Construction equipment Agricultural equipment Recreational vehicles	Temperature Range: -30°C to +170°C
	Specifications: ELV & RoHS compliant	

Housing: Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate	Race: GR-Nylon, LV-3H	Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
--	-----------------------	--

Part No.	Bore Size	C	W	H	D	O	Liner	Static Load Rating (Newtons) Radial
DB-SA-170	8	62.5	12	9.8	22	10.4	GR-NYLON	12,775

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060556974
Inside diameter	8 mm
Inside diameter	0.315" inch
Outside diameter	82.5 mm
Outside diameter	3.248" inch
Thickness	12 mm
Thickness	0.472" inch
Type	SI
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE