

## SI Rod end

# DB-SA-355-DUNLOP - DB-SA-355-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/si/db-sa-355-dunlop>

MALE ROD ENDS

**DB SERIES: DBM - DBI**

**Description:**  
DB-Series is our 3-piece 'dog bone' range of rod ends primarily based on our MP-Series with regards to function and structure. A wide range of preset centre distances are available. Suitable for light to medium industrial/mechanical load applications requiring low friction, with good wear resistance and available in both metric and imperial bore sizes. They have excellent moisture resistance and require no maintenance.

**Material Specifications:**  
Housing: Steel 230M07PB zinc plated and clear trivalent passivate.  
Race: GR-Nylon LV-3H. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated.

**Features:**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating  
Good wear resistance  
Excellent moisture resistance  
No maintenance

**Possible Applications:**  
Light to medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles

**Temperature Range:**  
-30°C to +170°C

**Specifications:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB, Zinc Plated and Clear Trivalent Passivate

**Race:** GR-Nylon, LV-3H

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

| Part No.  | Bore Size | C     | W  | H    | D  | O    | Liner           | Static Load Rating (Newtons) Radial |
|-----------|-----------|-------|----|------|----|------|-----------------|-------------------------------------|
| DB-SA-355 | 12        | 151.0 | 16 | 12.0 | 30 | 15.4 | SINTERED BRONZE | 22,700                              |

## PRODUCT FEATURES

|                  |                   |
|------------------|-------------------|
| Brand            | DUNLOP            |
| N° Ean13         | 3616060557063     |
| Inside diameter  | 12 mm             |
| Outside diameter | 151 mm            |
| Thickness        | 16 mm             |
| Type             | SI                |
| Thread           | Right-hand thread |
| Lubrication      | with              |
| Packaging        | 1                 |

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE