

## GE Rod end GE40-FW-DUNLOP - GE40-FW-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge40-fw-dunlop>

SPHERICAL BEARINGS

**GE FW SERIES**

**Description:**  
GE-FW Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low friction  
High shock loads  
Extended wear life  
No maintenance

**Possible Applications:**  
Medium/Heavy Industrial/  
mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control.

**Temperature Range:**  
-53°C to +121°C

**Specifications:**  
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened      Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE40FW		40	40	25	68	608,000

### PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060557247
Inside diameter	40 mm
Outside diameter	68 mm
Thickness	40 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE