

GE Rod end GE90-FW-DUNLOP - GE90-FW-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/ge90-fw-dunlop>

SPHERICAL BEARINGS




GE FW SERIES

Description:
GE-FW Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/Heavy Industrial/ mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range:
-53°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE90FW		90	85	55	130	2,842,000

PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	3616060557377
Inside diameter	90 mm
Outside diameter	85 mm
Thickness	55 mm
Type	GE
Thread	Right-hand thread
Lubrication	with
Packaging	1

contact@123bearing.co.uk

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE