

# GE Rod end GEZ012-ES-2RS-DUNLOP - GEZ012-ES-2RS-DUNLOP

<https://www.123bearing.co.uk/bearing-housing/rod-end/ge/gez012-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

**GEZ ES SERIES**



**Description:**  
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS2 for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS2. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Hydraulic applications

**Temperature Range:**  
-34°C to +121°C

**Specifications:**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS2.

**Ball:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seals:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ012ES-2RS	3/4	14.642	14.275	31.750	95,000

## PRODUCT FEATURES

Brand	DUNLOP
N° Ean13	5059161262333
Inside diameter	19.05 mm
Outside diameter	31.75 mm
Thickness	14.27 mm
Type	GE
Weight	50 g
Thread	Right-hand thread
Lubrication	with
Packaging	1
Standard	No standard

[contact@123bearing.co.uk](mailto:contact@123bearing.co.uk)

02038 087 274

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE